Perry Fiberglass Products, Inc.

LEADERS IN THE DESIGN AND MANUFACTURING OF DUCTWORK, CARBON ADSORBERS, SCRUBBERS, FANS, PIPING, & TANKS

5415 Village Drive Rockledge, Florida 32955 / PHONE: 321-609-9036 / FAX: 321-609-9003 / www.PerryFiberglass.com

AIRSORB W-PA 60-HS-0.3 MEDIA

Technical Data Sheet

About AIRSORB W-PA 60-HS-0.3 Media:

Perry AIRSORB W-PA 60-HS 0.3 is a highly active palletized carbon. Perry AIRSORB W-PA 60-HS 0.3, has an extremely high adsorption capacity for hydrogen sulfide and is used in variety of odor control applications within the paper, food and waste water treatment industries. The product also has a high hardness and low pressure drop characteristics.

1.25

60

0.3

97

15% 28 lb/ft³

0.48-0.50

4mm or 3mm

Applications:

- Odor Control
- Industrial and Municipal Waste Water and Sewage Plants
- Paper
- Food
- Process Treatment Facilities
- Gas Processing
- VOC Remediation

TYPICAL PHYSICAL PROPERTIES / SPECIFICATIONS:

Pressure Drop @ velocity 60 ft/min-ins wg/ft (4mm) CCl₄ Activity, Min. (ASTM D-3467) Hydrogen sulfide capacity min-gm/cc Apparent Density (ASTM D-2854), g/cc Hardness, Min. (ASTM D-3802) Particle Size Moisture, Max. (ASTM D-2867) Density

Typical Pressure Drop (4 mm Pellet)



supersacks Cylindrical Pellet LOW cost

PERRY AIRSORB W-PA 60-HS-0.3 MEDIA

Product Advantages:

- Longer service life unlike other activated carbon products.
- Shipped in 55lb and 1,100lb

This information is offered solely for your consideration and verification. It has been gathered from reference materials and/or test procedures and is believed to be true and accurate. None of this information shall constitute a warranty or representation, expressed or implied for which we assume legal responsibility or that the information or goods is fit for any particular use either alone or in combination with other goods or processes.